



MEDIUM FORM QUESTIONNAIRE

Date updated:	Dec 10, 2018		
Vessel name (IMO number):	American Bulker (IMO: 9736420)		
Ship Type:	Boxshaped Log bulkcarrier		
Class:	Nippon Kaiji Kyokai		
Flag:	Panama		
Year Built / Yard:	2016, Shikoku Dockyard Co., Ltd.		
Communications:	Call sign: 3FTG4		
	Telex: 437450610		
	Fax: 783400451		
	Phone: 773407694		
	Email: master.americanbulker@amosconnect.com		
Loadlines:	Dwat (mt)	Draft (m)	TPC
Summer Salt Water:	36,227.90	10.13	48.18
Winter Salt Water:	35,215.40	9.92	48.01
Tropical Salt Water:	37,243.10	10.34	48.33
Cargo capacities:	Grain (Cubic Meters)		Bale (Cubic Meters)
No. 1:	6,139.96		5,875.25
No. 2:	9,831.92		9,570.43
No. 3:	9,938.60		9,671.37
No. 4:	9,938.63		9,671.35
No. 5:	8,875.50		8,641.35
Total:	44,724.61		43,429.75
Holds/Hatches:	5 / 5		
Hatch cover type:	Kyoritsukikai Co., Ltd. / HYdraulic		
Hatch dimensions	Hatch #1: 14.00 m X 16.00 m Hatch #2, #3, #4, #5: 20.00 m X 20.40 m		
Cranes number/capacity/type:	4 x 31.2 MT / IHI, H312185-240		
Grabs number/capacity/type:			
Speed and Consumption			
At sea laden condition:	Abt. 13.20 kts on abt 20.70 mt IFO RMG380 and 0.20 mt MGO DMA max 0.10% sulphur		
At sea ballast condition:	Abt. 14.00 kts on abt 20.70 mt IFO RMG380 and 0.20 mt MGO DMA max 0.10% sulphur		
	Under good weather conditions up to Beaufort 4 and Douglas Sea State 3		
In port when idle:	2.30 mt IFO RMG380 and 0.20 mt MGO DMA max 0.10% sulphur		
In port when working:	4.80 mt IFO RMG380 and 0.20 mt MGO DMA max 0.10% sulphur		
Vessel is allowed to consume MGO DMA max 0.10% sulphur when starting/stopping and maneuvering in narrow/shallow water			
	In EU ports, vessel must burn MGO DMA max 0.10% sulphur instead of MDO and IFO - idle and working.		
	Bunkers on board always to comply with ISO standard 8217:2005 or latest revision/amendments.		
Loa/Beam:	179.80m / 30.40m		
International GT/NT:	22,426.00 / 11,365.00		
Panama Canal NT:	22,426.00		
Suez Canal GT/NT:	22,731.34 / 20,408.38		
Bunker tank capacities:	1,480.80 CBM (IFO RMG380) 187.64 CBM (MGO DMA max 0.10% sulphur) (always to be confirmed by master)		
Constants:	180 mt excl. fresh water (always to be confirmed by master)		
Tank Strengths:	Tank Top	Deck	Hatch Cover
	25.0 MT/sqm	MT/sqm	Hatch #1: 2.78 MT/sqm Hatch #2: 3.00 MT/sqm Hatch #3, #4, #5: 3.22 MT/sqm
Other fittings:			
Logs fitted	Yes		
Cement holes:	2, Dia 700		
Electrical ventilation:	Yes		
Grain fitted	Yes		
Are holds CO2 fitted:	Yes		
A60 bulkhead:	Yes		
Australian hold ladder	Yes		
Strengthened for heavy cargo:	Yes	Holds left empty:	No.2 & 4

All information about and believed to be correct.

J. Lauritzen A/S • 15 Tuborg Havnevej • 2900 Hellerup • Denmark