

**MEDIUM FORM QUESTIONNAIRE**

Date updated:	Dec 10, 2018		
Vessel name (IMO number):	Iberian Bulker (IMO: 9782962)		
Ship Type:	Boxshaped Log bulkcarrier		
Class:	Nippon Kaiji Kyokai		
Flag:	Marshall Islands		
Year Built / Yard:	2017, I-S SHIPYARD CO.,LTD		
Communications:	Call sign: V7WR5		
	Telex:		
	Fax: 870783971319		
	Phone: 870773208293		
	Email: V7WR5@globeemail.com;		
Loadlines:	Dwat (mt)	Draft (m)	TPC
Summer Salt Water:	37,668.00	10.54	48.60
Winter Salt Water:	36,605.00	10.32	48.46
Tropical Salt Water:	38,733.00	10.76	48.70
Cargo capacities:	Grain (Cubic Meters)		Bale (Cubic Meters)
No. 1:	7,707.42		7,380.05
No. 2:	9,932.74		9,575.67
No. 3:	9,966.82		9,578.52
No. 4:	9,955.17		9,577.94
No. 5:	9,432.71		9,126.15
Total:	46,994.86		45,238.33
Holds/Hatches:	5 / 5		
Hatch cover type:	Steel hatch cover/ Water Tight Folding type.		
Hatch dimensions	Hatch #1: 15.865 X17.16 Hatch #2, #3, #4, #5: 20.04 X20.02		
Cranes number/capacity/type:	4 x 30.5 MT / CRANE		
Grabs number/capacity/type:			
Speed and Consumption			
At sea laden condition:	Abt. 14.2 kts on abt 23.8 mt IFO 380 CST and 0.1 mt LSGO		
At sea ballast condition:	Abt. 14.8 kts on abt 23.8 mt IFO 380 CST and 0.1 mt LSGO		
	Under good weather conditions up to Beaufort 4 and Douglas Sea State 3		
In port when idle:	2.8 mt IFO 380 CST and 0.1 mt LSGO		
In port when working:	6.4 mt IFO 380 CST and 0.1 mt LSGO		
Vessel is allowed to consume LSGO when starting/stopping and maneuvering in narrow/shallow water			
	In EU ports, vessel must burn LSGO instead of MDO and IFO - idle and working.		
	Bunkers on board always to comply with ISO standard 8217:2005 or latest revision/amendments.		
Loa/Beam:	179.97m / 29.831m		
International GT/NT:	23,242.00 / 12,101.00		
Panama Canal NT:	0.00		
Suez Canal GT/NT:	0.00 / 0.00		
Bunker tank capacities:	0.00 CBM (IFO 380 CST) 0.00 CBM (LSGO) (always to be confirmed by master)		
Constants:	220 mt excl. fresh water (always to be confirmed by master)		
Tank Strengths:	Tank Top	Deck	Hatch Cover
	Hold #1: 20.68 MT/sqm Hold #2, #4: 15.05 MT/sqm Hold #3: 20.0 MT/sqm Hold #5: 20.08 MT/sqm	MT/sqm	
Other fittings:			
Logs fitted	Yes		
Cement holes:	2pcs, DIAMETER 0.85M, FORE PORT SIDE, STARBOARD AFTER		
Electrical ventilation:	No		
Grain fitted	Yes		
Are holds CO2 fitted:	Yes		
A60 bulkhead:	Yes		
Australian hold ladder	Yes		
Strengthened for heavy cargo:	Yes	Holds left empty:	2&4

All information about and believed to be correct.

J. Lauritzen A/S • 15 Tuborg Havnevej • 2900 Hellerup • Denmark