

**MEDIUM FORM QUESTIONNAIRE**

Date updated:	Dec 10, 2018		
Vessel name (IMO number):	Spinnaker Sw (IMO: 9580003)		
Ship Type:	Bulkcarrier		
Class:	Nippon Kaiji Kyokai		
Flag:	Panama		
Year Built / Yard:	2012, The Hakodate Dock CO.,LTD		
Communications:	Call sign: 3EJV6		
	Telex:		
	Fax: 783208008		
	Phone: 437201410		
	Email: 3evv6@swnav.amosconnect.com		
Loadlines:	Dwat (mt)	Draft (m)	TPC
Summer Salt Water:	31,657.00	9.64	45.21
Winter Salt Water:	30,754.00	9.44	45.04
Tropical Salt Water:	32,563.00	9.84	45.39
Cargo capacities:	Grain (Cubic Meters)		Bale (Cubic Meters)
No. 1:	5,492.77		5,415.66
No. 2:	9,077.99		8,875.34
No. 3:	9,077.99		8,875.84
No. 4:	8,961.51		8,490.67
No. 5:	7,883.23		7,811.03
Total:	40,493.49		39,468.54
Holds/Hatches:	5 / 5		
Hatch cover type:	Folding Type		
Hatch dimensions	Hatch #1: 12.75 x 13.60 Hatch #2, #3, #4, #5: 19.55 x 19.60		
Cranes number/capacity/type:	4 x 30 MT / Crane MITSUBISHI Electro-Hydraulic		
Grabs number/capacity/type:			
Speed and Consumption			
At sea laden condition:	Abt. 13.2 kts on abt 24 mt 380 cst HFO and 0.1 mt LSMGO		
At sea ballast condition:	Abt. 14 kts on abt 23.5 mt 380 cst HFO and 0.1 mt LSMGO		
	Under good weather conditions up to Beaufort 4 and Douglas Sea State 3		
In port when idle:	1.7 mt 380 cst HFO and 0.2 mt LSMGO		
In port when working:	3.8 mt 380 cst HFO and 0.2 mt LSMGO		
Vessel is allowed to consume LSMGO when starting/stopping and maneuvering in narrow/shallow water			
	In EU ports, vessel must burn LSMGO instead of MDO and IFO - idle and working.		
	Bunkers on board always to comply with ISO standard 8217:2005 or latest revision/amendments.		
Loa/Beam:	175.53m / 29.4m		
International GT/NT:	19,836.00 / 10,404.00		
Panama Canal NT:	16,561.00		
Suez Canal GT/NT:	0.00 / 0.00		
Bunker tank capacities:	0.00 CBM (380 cst HFO) 0.00 CBM (LSMGO) (always to be confirmed by master)		
Constants:	270 mt excl. fresh water (always to be confirmed by master)		
Tank Strengths:	Tank Top	Deck	Hatch Cover
	Hold #1: 19.5 MT/sqm Hold #2, #4: 15.13 MT/sqm Hold #3: 20.45 MT/sqm Hold #5: 19.05 MT/sqm	4.0 MT/sqm	Hatch #1: 2.50 MT/sqm Hatch #2, #3, #4, #5: 2.87 MT/sqm
Other fittings:			
Logs fitted	Yes		
Cement holes:	2PC 700mm, Center		
Electrical ventilation:	Yes		
Grain fitted	Yes		
Are holds CO2 fitted:	Yes		
A60 bulkhead:	No		
Australian hold ladder	Yes		
Strengthened for heavy cargo:	Yes	Holds left empty:	No.2 & No.4 Hold

All information about and believed to be correct.

J. Lauritzen A/S • 15 Tuborg Havnevej • 2900 Hellerup • Denmark