



MEDIUM FORM QUESTIONNAIRE

Date updated:	Dec 10, 2018		
Vessel name (IMO number):	AC Kathryn (IMO: 9310745)		
Ship Type:	Log bulkcarrier		
Class:	Nippon Kaiji Kyokai		
Flag:	Panama		
Year Built / Yard:	2006, Kanda Shipbuilding Co., Ltd.		
Communications:	Call sign: 3EGJ		
	Telex:		
	Fax:		
	Phone: 870773230659		
	Email: ansackathryn@sinceremarine.amosconnect.com		
Loadlines:	Dwat (mt)	Draft (m)	TPC
Summer Salt Water:	32,727.51	10.02	43.84
Winter Salt Water:	31,816.37	9.81	43.66
Tropical Salt Water:	33,642.34	10.23	44.01
Cargo capacities:	Grain (Cubic Meters)		Bale (Cubic Meters)
No. 1:	6,834.00		6,455.00
No. 2:	9,165.00		8,744.00
No. 3:	9,170.00		8,746.00
No. 4:	9,170.00		8,746.00
No. 5:	8,518.00		8,205.00
Total:	42,857.00		40,896.00
Holds/Hatches:	5 / 5		
Hatch cover type:	NAKATA MAC CORPORATION / Folding Type		
Hatch dimensions	Hatch #1: 15.20x15.80 Hatch #2, #3, #4, #5: 20.00x19.00		
Cranes number/capacity/type:	4 x 30.5 MT / IHI, Electric-Hydraulic Single Type		
Grabs number/capacity/type:			
Speed and Consumption			
At sea laden condition:	Abt. 14.00 kts on abt 25.2 mt 380cst hfo and 0.1 mt lsmgo		
At sea ballast condition:	Abt. 14.6 kts on abt 25.2 mt 380cst hfo and 0.1 mt lsmgo		
	Under good weather conditions up to Beaufort 4 and Douglas Sea State 3		
In port when idle:	2.2 mt 380cst hfo and 0.1 mt lsmgo		
In port when working:	5.2 mt 380cst hfo and 0.1 mt lsmgo		
Vessel is allowed to consume lsmgo when starting/stopping and maneuvering in narrow/shallow water			
	In EU ports, vessel must burn lsmgo instead of MDO and IFO - idle and working.		
	Bunkers on board always to comply with ISO standard 8217:2005 or latest revision/amendments.		
Loa/Beam:	177m / 28.4m		
International GT/NT:	19,885.00 / 11,140.00		
Panama Canal NT:	16,603.00		
Suez Canal GT/NT:	20,321.43 / 18,280.94		
Bunker tank capacities:	1,146.92 CBM (380cst hfo) 95.73 CBM (lsmgo) (always to be confirmed by master)		
Constants:	200 mt excl. fresh water (always to be confirmed by master)		
Tank Strengths:	Tank Top	Deck	Hatch Cover
	12 MT/sqm	4.0 MT/sqm	Hatch #1: 2.8 MT/sqm Hatch #2, #3, #4, #5: 3.0 MT/sqm
Other fittings:			
Logs fitted	Yes		
Cement holes:	2 X 780 mm		
Electrical ventilation:	No		
Grain fitted	Yes		
Are holds CO2 fitted:	Yes		
A60 bulkhead:	No		
Australian hold ladder	Yes		
Strengthened for heavy cargo:	No	Holds left empty:	

All information about and believed to be correct.

J. Lauritzen A/S • 15 Tuborg Havnevej • 2900 Hellerup • Denmark