



MEDIUM FORM QUESTIONNAIRE

Date updated:	Mar 23, 2019		
Vessel name (IMO number):	Se Cardi (IMO: 9846316)		
Ship Type:			
Class:	Nippon Kaiji Kyokai		
Flag:	Panama		
Year Built / Yard:	2019, Shimanami Shipyard		
Communications:	Call sign: 3EGB7		
	Telex:		
	Fax: +870 783 247 898		
	Phone: +870 773 701 913		
	Email: secardi@sinceremarine.amosconnect.com		
Loadlines:	Dwat (mt)	Draft (m)	TPC
Summer Salt Water:	37,717.00	10.54	48.60
Winter Salt Water:	36,654.00	10.32	48.50
Tropical Salt Water:	38,782.00	10.76	48.70
Cargo capacities:	Grain (Cubic Meters)	Bale (Cubic Meters)	
No. 1:	7,707.42	7,380.05	
No. 2:	9,932.74	9,575.67	
No. 3:	9,966.82	9,578.52	
No. 4:	9,955.17	9,577.94	
No. 5:	9,963.50	9,126.15	
Total:	47,525.65	45,238.33	
Holds/Hatches:	5 / 5		
Hatch cover type:	IMABARI SHIPBUILDIND CO.,LTD. HYD. CYL. DRIVE SYS.		
Hatch dimensions	Hatch #1: 15.865 X 17.160 Hatch #2, #3, #4, #5: 20.040 X 20.020		
Cranes number/capacity/type:	4 x 30.5 MT / MHI / Machinery, Electric		
Grabs number/capacity/type:			
Speed and Consumption	To be advised		
Loa/Beam:	179.97m / 29.80m		
International GT/NT:	23,232.00 / 12,101.00		
Panama Canal NT:	19,355.00		
Suez Canal GT/NT:	23,765.37 / 21,505.84		
Bunker tank capacities:	1,775.28 CBM (380 cst at 50) 170.57 CBM (low sulphur gas oil 0.1%) (always to be confirmed by master)		
Constants:	mt excl. fresh water (always to be confirmed by master)		
Tank Strengths:	Tank Top	Deck	Hatch Cover
	Hold #1: 20.68 MT/sqm Hold #2, #4: 15.05 MT/sqm Hold #3, #5: 20.00 MT/sqm	4.62 MT/sqm	3.30 MT/sqm
Other fittings:			
Logs fitted	Yes		
Cement holes:	2, 700MM, P/F 7 amp; S/A		
Electrical ventilation:	No		
Grain fitted	Yes		
Are holds CO2 fitted:	Yes		
A60 bulkhead:	Yes		
Australian hold ladder	Yes		
Strengthened for heavy cargo:	Yes	Holds left empty:	No.2 & No.4 Holds

All information about and believed to be correct.

J. Lauritzen A/S • 15 Tuborg Havnevej • 2900 Hellerup • Denmark